

IN THE CLAIMS

1 1 (currently amended). A decorative cabinet door assembly comprising:

2 a generally rectangular frame including an upper frame member, a
3 lower frame member, a pair of opposing side members and an open space
4 defined between said upper frame member, said lower frame member and said
5 pair of opposing side members, one of said upper frame member and said lower
6 frame member having a slot therein extending between an inner edge adjacent
7 said open space and an opposed outer edge of said one of said upper frame
8 member and said lower frame member;

9 a flexible sheet panel covering said open space and removably
10 extending straight through said [a] slot in one of said upper frame member and
11 said lower frame member to said an outer edge of said one of said upper frame
12 member and said lower frame member, said flexible sheet panel also extending
13 straight into an inner edge adjacent said open space of the other an opposed
14 one of said upper frame member and said lower frame [a] member,

15 a sheet panel support disposed along said an outer edge of said one of
16 said upper frame member and said lower frame member having said slot
17 therein, and a sheet panel support and tensioner disposed in the other an
18 opposite one of said upper frame member and said lower frame member,

19 whereby said flexible sheet panel is supported and stretched between
20 said outer edge of said one of said upper frame member and said lower frame
21 member and the other an opposed said one of said upper frame member and
22 said lower frame member.

1 2 (previously presented). The assembly as defined in claim 1 wherein said
2 flexible sheet comprises a changeable decorative fabric sheet panel.

1 3 (cancelled).

1 4 (currently amended). The assembly as defined in claim 2 wherein said fabric
2 sheet panel support comprises:

3 a first ~~an upper~~, tubular loop contiguous with and formed at one end
4 of ~~from~~ said fabric sheet panel and extending a width ~~length~~ of an upper edge
5 of said of said fabric sheet panel,

6 ~~a lower, tubular loop contiguous with and formed from said fabric~~
7 ~~sheet panel and extending a length of a lower edge of said panel,~~

8 a first dowel pin inserted through said tubular upper loop, and;

9 ~~a second dowel pin inserted through said lower loop,~~

10 a groove along said opposed outer edge of said one of said upper
11 frame member and said lower frame member, said groove communicating along
12 its length with an outer edge of said one of said upper frame member and said
13 ~~lower frame member and communicating in parallel relation with said slot~~
14 ~~through which one of said first upper tubular loop and said lower tubular loop~~
15 ~~extends, said groove sized to receive said first dowel pin and said second dowel~~
16 ~~pin, so that a respective said first dowel pin is insertable through a said~~
17 ~~tubular first tubular loop or second tubular loop after said first tubular loop is~~
18 ~~passed through said slot, thereby securing supporting said fabric sheet panel~~

19 in place in said one of said upper frame member and said lower frame member.

1 5 (cancelled).

1 6 (cancelled).

1 7 (cancelled).

1 8 (cancelled).

1 9 (cancelled).

1 10 (currently amended). The assembly as defined in claim 12 wherein said
2 fabric sheet panel has a length enabling said ~~lower~~ dowel pin to hold said fabric
3 sheet panel tightly in place.

1 11 (previously presented). The assembly as defined in claim 15 wherein said
2 door is made of wood.

1 12 (currently amended). The assembly as set forth in claim 4 wherein said
2 sheet panel support and tensioner comprises an opposed said one of said
3 upper frame member and said lower frame member from a said one of said
4 upper frame member and said lower frame member having said slot and said

5 groove therein being is configured having a recess along an inner side thereof,
6 said recess extending generally the width of said fabric sheet panel, with an
7 inner surface of said recess being coplanar with said slot, and opposed notches
8 at lower outer regions of said recess, and further comprising a second tubular
9 loop at an opposed end of said fabric sheet panel from said first tubular loop,
10 said second tubular loop contiguous with and extending a width of said fabric
11 sheet panel, and wherein a second said dowel pin insertable into said second
12 loop wherein ~~of said first dowel pin and~~ said second dowel pin is slightly longer
13 than a length of said loop in said recess so that said second dowel pin extends
14 a length of said recess and ends of said second dowel pin engage said opposed
15 notches, securing said fabric sheet panel in said coplanar relation with said
16 inner surface of said recess and tensioning said fabric sheet panel between said
17 upper frame member and said lower frame member.

1 13 (previously presented). The assembly as defined in claim 12 wherein said
2 fabric sheet panel is wider than said open space.

1 14 (currently amended). The assembly as defined by claim 13 wherein said
2 opposing side members each have a narrow slot in an inner edge thereof ~~of~~
3 ~~each of said opposing side members,~~ said narrow slot being coplanar with said
4 slot in said one of said upper frame member and said lower frame member and
5 said inner surface of said recess, with side edges of said fabric sheet panel
6 extending into each said narrow slot.

1 15 (previously presented). The assembly as defined by claim 14 wherein said
2 fabric sheet panel is unsupported in each said narrow slot in said inner edges
3 of said opposing side members.

Please add the following new claims to the application.

1 16 (new). A decorative cabinet door assembly made of wood and having a
2 removable flexible decorative sheet panel and comprising:
3 a generally rectangular frame including an upper frame member, a
4 lower frame member, a pair of opposing side members and an open space
5 defined between said upper frame member, said lower frame member and said
6 pair of opposing side members, one of said upper frame member and said lower
7 frame member having a slot therein extending between an inner edge adjacent
8 said open space and an opposed outer edge of said one of said upper frame
9 member and said lower frame member, and a groove along said opposed outer
10 edge of said one of said upper frame member and said lower frame member,
11 said groove communicating along its length with said slot, and the other of said
12 upper and lower frame members configured having a recess along an inner side
13 thereof, said recess extending generally a width of said flexible decorative sheet
14 panel, with an inner surface of said recess along said inner side being coplanar
15 with said slot, and opposed notches at lower outer regions of said recess, and
16 each side member of said pair of opposing side members having a slot along an
17 inner side thereof adjacent said open space, each said slot in each said side
18 member being coplanar with said slot in said one of said upper frame member

19 and said lower frame member and said inner surface of said recess,
20 said flexible decorative sheet panel covering said open space and
21 removably extending straight through said slot to said outer edge of said one of
22 said upper frame member and said lower frame members, said flexible
23 decorative sheet panel also extending straight into said inner surface of said
24 recess of the other of said upper frame member and said lower frame member,
25 and further extending on each side into said slot of each of said opposing side
26 members, said flexible decorative sheet panel having a first tubular loop
27 extending through said slot in said one of said upper frame member and said
28 lower frame member and contiguous with and formed at one end of said
29 flexible decorative sheet panel and extending a width of said flexible decorative
30 sheet panel, and a second tubular loop at an opposed end of said flexible
31 decorative sheet panel from said first tubular loop and contiguous with and
32 extending a width of said flexible decorative sheet panel,
33 a first dowel pin insertable through said first tubular loop after said
34 first tubular loop is passed through said slot in said one of said upper frame
35 member and said lower frame member, with said groove sized to receive said
36 first dowel pin, thereby supporting said flexible decorative sheet panel in place
37 in said one of said upper frame member and said lower frame member, and a
38 second dowel pin slightly longer than a length of said recess so that said dowel
39 pin extends a length of said recess and ends of said dowel pin engage said
40 opposed notches, with said second dowel pin insertable through said second
41 loop and securing said flexible decorative sheet panel in said coplanar relation

42 with said inner surface of said recess and tensioning said flexible decorative
43 sheet panel between said upper frame member and said lower frame member.

1 17 (new). A decorative cabinet door assembly made of wood as set forth in
2 claim 16 wherein said flexible decorative sheet panel extends unsupported into
3 each said slot of each of said pair of opposing side members.

1 18 (new). A decorative cabinet door assembly made of wood and comprising:
2 a generally rectangular frame including an upper frame member, a
3 lower frame member, a pair of opposing side members and an open space
4 defined between said upper frame member, said lower frame member and said
5 pair of opposing side members, one of said upper frame member and said lower
6 frame member having a slot therein extending along and between an inner edge
7 adjacent said open space and an opposed outer edge of said one of said upper
8 frame member and said lower frame member, and a groove along said opposed
9 outer edge of said one of said upper frame member and said lower frame
10 member, said groove communicating along its length with said slot, and the
11 other of said upper and lower frame members configured having a recess along
12 an inner side thereof, with an inner surface of said recess being coplanar with
13 said slot, and opposed notches at lower outer regions of said recess, and said
14 opposing side members each having a narrow slot along an inner edge thereof
15 adjacent said open space, each said narrow slot in said opposing side members
16 being coplanar with said slot and said inner surface of said recess,

17 a flexible decorative sheet panel covering said open space and
18 removably extending straight through said slot to said outer edge of said one of
19 said upper frame member and said lower frame member, said flexible
20 decorative sheet panel also extending straight into said recess of the other of
21 said upper frame member and said lower frame member, said flexible
22 decorative sheet panel having a first tubular loop extending through said slot
23 and contiguous with and formed at one end of said flexible decorative sheet
24 panel and extending a width of said flexible decorative sheet panel, and a
25 second tubular loop at an opposed end of said flexible decorative sheet panel
26 from said first tubular loop and contiguous with and extending a width of said
27 flexible decorative sheet panel, said flexible decorative sheet panel being
28 slightly wider than said open space so that side edges thereof extend
29 unsupported into each said narrow slot in said opposing side members,

30 a first dowel pin insertable through said first tubular loop after said
31 first tubular loop is passed through said slot, with said groove sized to receive
32 said first dowel pin, thereby supporting said flexible decorative sheet panel in
33 place in said one of said upper frame member and said lower frame member,
34 and a second dowel pin insertable through said second loop and slightly longer
35 than a length of said recess so that said second dowel pin extends a length of
36 said recess and ends of said second dowel pin engage said opposed notches,
37 securing said flexible decorative sheet panel in said coplanar relation with said
38 inner surface of said recess and tensioning said flexible sheet panel between
39 said upper frame member and said lower frame member.